

Sukup 2300 Grain Drill Specifications

Drill Model	# of Openers	Row Spacing	Planting Width	Transport Width	Weight* (lbs.)
5'	8	7-1/2"	5'	5'7"	1560
3-pt Conv.	10	6"	5'	5'7"	1700
5'	8	7-1/2"	5'	5'7"	2045
3-pt. No-Till	10	6"	5'	5'7"	2275
5' Pull Conv.	8	7-1/2"	5'	7'6"	2400
"	10	6"	5'	7'6"	2550
5' Pull No-Till	8	7-1/2"	5'	7'6"	2885
"	10	6"	5'	7'6"	3145
7' 3-pt. Conv.	10	7-1/2"	6'3"	7'10"	2160
"	12	6-2/3"	6'8"	7'10"	2300
"	12	7-1/2"	7'6"	7'10"	2300
7' 3-pt. No-Till	10	7-1/2"	6'3"	7'10"	2735
"	12	6-2/3"	6'8"	7'10"	2965
"	12	7-1/2"	7'6"	7'10"	2965
7' Pull Conv.	10	7-1/2"	6'3"	7'10"	2490
"	12	6-2/3"	6'8"	7'10"	2630
"	12	7-1/2"	7'6"	7'10"	2630
7' Pull No-Till	10	7-1/2"	6'3"	7'10"	2940
"	12	6-2/3"	6'8"	7'10"	3170
"	12	7-1/2"	7'6"	7'10"	3170
10' 3-pt Conv.	16	7-1/2"	10'	10'7"	2850
"	18	6-2/3"	10'	10'7"	2990
10' 3-pt. No-Till	16	7-1/2"	10'	10'7"	3820
"	18	6-2/3"	10'	10'7"	4050
10' Pull Conv.	16	7-1/2"	10'	10'7"	3350
"	18	6-2/3"	10'	10'7"	3490
10' Pull No-Till	16	7-1/2"	10'	10'7"	4070
"	18	6-2/3"	10'	10'7"	4300
15' 3-pt Conv.	24	7-1/2"	15'	15'3"	4125
15' 3-pt. No-Till	24	7-1/2"	15'	15'3"	5420
15' Pull Conv.	24	7-1/2"	15'	15'3"	4435
15' Pull No-Till	24	7-1/2"	15'	15'3"	5730

This information is intended to assist you in choosing the optimal equipment for your situation. Many factors can affect the operation of agricultural equipment and your results may vary. Thus, this information is not a guarantee of product specifications or performance. Based on these factors, Sukup specifications should only be used as estimates, and not as a warranty, express or implied, of how a particular Sukup unit will perform under your operating conditions. Because Sukup is constantly improving our products, changes may occur that may not be reflected in the specifications.