

Sukup 4200 Cultivator Specifications

Model	Row Width	Weight (lbs)	Transport Height	Transport Width
4-Row rigid	30"	1675	-	11'5"
"	36" - 38"	1750	-	14'1"
"	38" - 40"	1775	-	14'9"
6-Row rigid	30"	2200	-	16'5"
"	36" - 38"	2275	-	20'5"
"	38" - 40"	2300	-	21'5"
8-row Rigid	30"	2700	-	21'5"
"	36" - 38"	2825	-	26'9"
"	38" - 40"	2850	-	28'1"
8-Row Fold	30"	3375	9'2"	13'4"
"	36" - 40"	3700	10'2"	16'5"
10-Row Fold	30"	4075	-	26'9"
"	36" - 38"	4200	-	33'1"
12-Row Fold	30"	4575	10'6"	18'0"
"	36" - 38"	5800	11'6"	22'6"
16-Row Fold	30"	6700	14'0"	17'8"
24-Row Fold	22"	10,000	14'0"	21'5"

This information is intended to assist you in choosing the optimal equipment for your situation. Many factors can affect the operation of agricultural equipment and your results may vary. Thus, this information is not a guarantee of product specifications or performance. Based on these factors, Sukup specifications should only be used as estimates, and not as a warranty, express or implied, of how a particular Sukup unit will perform under your operating conditions. Because Sukup is constantly improving our products, changes may occur that may not be reflected in the specifications.